



2632SE

Electric Slim Scissor Lift

- Direct electric drive for extended duty cycles and faster drive speeds
- Standard integrated sheet material tray allows 110 lbs. (50 kg) to be stored and lifted outside the platform
- Compact maneuverability from front wheel drive and steer with zero inside turn radius
- Drivable at full height
- Fully proportional lift and drive controls
- Standard swing gate
- Easy serviceability with swing out battery and power module trays



Do More with Direct Electric Drive, Standard Sheet Material Tray and Single Doorway Access

Features

Work Area

Standard integrated sheet material tray designed and approved by the manufacturer
 Roll-out deck extension with incremental locking positions
 Standard swing gate
 Lanyard attachments (4)

Performance

Direct electric drive
 Fully proportional drive and lift controls

Power

24v 225Ah DC electric power
 Battery charge indicator

Serviceability

Lubrication-free scissor bearings
 Easy maintenance access to mechanical and electrical components in a slide-out tray
 Logically grouped components and numbered wiring for easy reference

Safety

Dedicated compartment protects electrical and hydraulic components
 Emergency shut-off at platform and lower controls
 Non-skid metal deck construction
 Descent alarm
 Drive speed interlock
 Multi-axis tilt sensor
 Scissor maintenance lock
 Multiple disc brakes

Other Features

Removable upper controls
 Voltage-compensating fully automatic battery charger
 Fold-down guardrails
 Hour meter
 Machine tie downs
 Non-marking tires
 All motion alarm
 Fork lift pocket
 U.S. Patent #8,678,135

Optional Features

Flashing beacon (continuous)
 900W Inverter
 2-Year extended warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

97015 DTD 1016

2632SE	U.S.	Metric
Heights		
Working Height*	32 ft.	10 m
Platform Height	26 ft.	8 m
Stowed Height (Top Guardrail)	91 in.	2.3 m
Stowed Height (Rails Folded)	78 in.	2 m
Stowed Height (Platform Floor)	48 in.	1.2 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	.7 in.	2 cm
Dimensions		
Length-Stowed (Overall)	97 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	32 in.	81 cm
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.27 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width (Outside Sheet Tray)	33 in.	84 cm
Wheelbase	74 in.	1.9 m
Total Lift Capacity (Including Tray)	500 lbs	227 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs	113 kg
Sheet Tray Capacity	110 lbs	50 kg
Speed		
Raise/Lower Speed	42 s / 30 s	
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	4,675 lbs.	2,120 kg
Power Source	24 v DC, 225Ah Battery pack	
Controls	Proportional drive & lift controls	
Tires	15 x 5 in.	38 x 13 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.6-2006 and CSA B354.4-02.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

