



# 45-AJ

## Articulated Boom

### Full-Featured, Rugged, Simple, Reliable

- 51 ft. (15.5 m) Working Height with Standard 5 ft. (1.5 m) Jib for 120° Jib Range of Motion
- Continuous 360° Rotation
- Solid Rough Terrain Tires
- Standard 6 ft. (1.8 m) Platform Including 3-Sided Entry with Swing Gate
- Powerful 4WD and Oscillating Front Axle Standard
- Proven Double-Riser Boom with Vertical Envelope Through First 25 ft. (7.6 m)



**Best in Class Productivity from Continuous Rotation**

## Standard Features

### Work Area

- 6 ft. (1.8 m) Platform Work Basket
- 3-Sided Entry with Swing Gate
- 500 lb. (227 kg) Platform Capacity
- 160° Platform Rotation
- 120° Jib Range of Motion
- Power to Platform

### Performance

- 360° Continuous Turntable Rotation
- 4WD Closed Loop Positive Traction Drive System
- 40% Gradeability
- Oscillating Axle
- Self-Leveling Platform
- Low Engine RPM Elevated Operation
- Two-Speed Drive Motors
- 51 ft. (15.5m) Working Height
- Full Drive Height

### Control System

- Triple Joystick Interface
- Fully Proportional Multi-Function Controls

### Power

- 48HP Kubota Diesel Engine

### Safety

- Emergency Shut-Off on Platform & Chassis
- Auxiliary Power Unit
- Multi-Axis Tilt Sensor
- Tilt Alarm and Horn
- Four Wheel SAHR Braking System
- Automotive Horn
- Engine Shut Down Protection

### Other Features

- Hour Meter
- Machine Tie-Downs and Lifting Lugs
- Powder Coat Finish
- Lanyard Attachments
- Standard Oil Cooler
- Standard Solid RT Tires
- Flashing Beacon



## Optional Features

- 3.5 KW AC Generator
- 2-Year Extended Warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

94541 DTD 0917

45-AJ Diesel	U.S.	Metric
<b>Heights</b>		
Working Height*	51 ft.	15.5 m
Platform Height	45 ft.	13.7 m
Maximum Outreach	25 ft. 1 in.	7.6 m
Up and Over Height	24 ft. 6 in.	7.5 m
Turntable Swing	Continuous	
Jib Range of Motion	65° Up / 55° Down	
Platform Rotation	160° (80° each side)	
<b>Platform Size &amp; Capacity</b>		
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2	
Platform Width	72 in.	1.8 m
Platform Depth	40 in.	1.0 m
Platform Entry	1 End Swing Gate, 2 Slide Bars	
<b>Dimensions</b>		
Length-Stowed (Overall)	23 ft. 10 in.	7.3 m
Width	91 in.	2.3 m
Overall Height	98 in.	2.5 m
Tailswing	Zero	
Weight (Approximately)	16,380 lbs.	7430 kg
<b>Working Conditions</b>		
Drive	4 Wheel Drive	
Gradeability	40%	
Ground Clearance	12 in.	30 cm
Axle Oscillation	20° (10° each direction)	
Tires	Solid (Non-Marking Optional)	
<b>Power</b>		
Power Source	48 HP Kubota Diesel	
Fuel Capacity	24 gal.	90 l
Hydraulic Oil Capacity	49 gal.	185 l
<b>Movement</b>		
Turning Radius (Inside/Outside)	6 ft. 6 in./16 ft. 1 in.	2.0 m/4.9m
Drive Speed	3.8 mph	6 kph
Lift Speed (Main Boom/Mid Boom)	34 seconds/38 seconds	
Boom Extend Speed	21 seconds	
Jib Lift Speed	22 seconds	

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Weight may vary with certain options or configurations.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.5-2006 and CSA B354.4-02 as applicable.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: